

CTF – FS

Fire safe overlay board

CTF FS 6mm rigid magnesium oxide overlay, site applied /factory laminated to CTF Therm ® product range, CTF ultra-VIP; CTF-01; CTF-02; CTF-03 and CTF-IV. To provide a robust and non-combustible substrate for single ply; torch applied, bituminous and liquid membranes. External surface spread of flame dependent upon waterproofing membrane specification.

Technical Data

U Values

Each scheme is individually designed to achieve the required U value. Contact our technical department for further information.

Installation

Must be installed in accordance with manufacturer's recommendations. Contact our technical department for further information and compatibility.

Features

- Fire performance BS EN 476 (parts 6 & 8) Class 0
- Fire performance Euroclass EN 13561 A1 non combustible
- Insulative (does not transfer heat)
- CTF, HFC, and HCFC – free
- Ozone Depletion Potential of Zero
- Global Warming Potential < 5
- Easy cutting and installation
- Recyclable

Technical Data

Thermal Conductivity	0.19W/mK
Compressive Strength	17.45mPa
Board Size	1200 x 800, 1200 x 2400
Thickness	6mm (others available)

The manufacturer reserves the right to alter these products. All data was produced under controlled test conditions. No warranty is implied or given as to the performance of these products in any variation from test conditions.